

Technical Support Notification

TLS-450PLUS & TLS4 Series CPU Backup Battery

Overview

The CPU backup battery on all TLS-450PLUS and TLS4 Series Automatic Tank Gauges (ATGs) has been changed due to supply chain issues. The previous ML2430 has been replaced with the ML2032 battery. The CPU backup battery allows the ATG to maintain its programmed date and time settings when the ATG is powered down. Batteries can still be ordered using part number 0330020-759.

Even though the ML2032 battery is slightly smaller in size, it is backwards compatible and will work with any TLS-450PLUS or TLS4 Series console.

Note: Before installing a ML2032 battery, the metal tab on the battery holder must be pushed in towards the CPU to ensure there is good contact between the battery and CPU.

Battery Specs

Previous Battery Model	Capacity (mAh)	Physical Size Diameter (mm) x Height (mm)	New Battery Model	Capacity (mAh)	Physical Size Diameter (mm) x Height (mm)
ML2430	100	24.5 x 3.0	ML2032	65	20.0 x 3.2





Note: Images are not to scale.

Further Information

- Contact Veeder-Root Technical Support at +1.800.323.1799 for additional help or questions.
- Learn more about the Automatic Tank Gauge Products on our website.

125 Powder Forest Drive • PO Box 2003 • Simsbury, CT 06070 • ©2022 Veeder-Root • P/N 576047-461

Technical Support Hours: M-F EST: 8am-7pm



technicalsupport@veeder.com



veeder.com/us/technical-support



+1.800.323.1799

